The Beri	tram Em	aine Wol	rks Comp	amy, Simited.
99000	00000	of Toronto.		
	requesi	ts the pleas	sure of	
my	M18 /6	as Par	in fr	
	presence	at the Law	inching of	2
The Re	chelieu F	Ontario Na	vigation Co	mpanys
	new Steer	l Passeng	er Steame	r
W.		Toron		
			e 21:st 1898.	
	at three	thirty o'c	lock, P.M.	
	The.	Bertram Eng	gine Works Co	mpany Limited.
		1	Caste 4.	Arbiace President.

Steamer" White Star with the invited guests will leave Geddes Wharf, foot of Bay St. promptly at three o'clock, P.M.

Please present this card at the Steamer.

The state of the s have a selection himself in man the superior to the same TOTAL TOTAL STATE OF THE STATE OF Mar July and the second and the second of the second of the second Santis Change of the second and the second of the said specific and second Commence of the second of the The same of the sa

THE BERTRAM ENGINE WORKS CO., LIMITED. TORONTO, CAN. President. Geo. H. Bertram, M.P. Vice-President. John Bertram, A. Angstrom, - - Engineer and Manager. COMMITTEE IN CHARGE OF CONSTRUCTION W. D. Matthews. Chairman. I. Kerr Osborne, Esq. Wm. Christie, Esq.

Frank E. Kirby

RECT	гоя		enera 	d Manager. Secretary. Montreal.
	ГОР	RS.		
	TOF	RS.		Montreal.
sq.,				Montreal.
sq.,				
		-	-	
		-	-	**
Esq.,			-	6.5
	-		-	- **
				**
,	-	-	-	Quebec.
-	-		-	Sorel.
	-	-		Kingston.
4.,	-	•		Toronto.
	Esq.,			

RICHELIEU & ONTARIO NAVIGATION CO.,

MONTREAL.

SIDE WHEEL PASSENGER STEEL STEAMER

Consult. Engineer.

"TORONTO"

THE BERTRAM ENGINE WORKS COMPANY, LIMITED,

FROM GENERAL DESIGNS BY A. ANGSTROM, ESQ., FOR THE

RICHELIEU & ONTARIO NAVIGATION COMPANY,

TO PLY ON THEIR ROUTE BETWEEN TORONTO AND MONTREAL.

GENERAL DATA.

HULL.

Is constructed of open hearth steel and of the tollowing dimensions:

Length over all		-	-			feet.
Length, keel -	-	-	-		270	4
Beam, moulded			-	-	36	
Beam, over guards			-	-	62	
Depth, moulded	-		-		14	44

ENGINES.

Ot the Triple Expansion, Inclined Jet-Condensing Type; cylinders 28, 44 and 74 inches by 72 inch stroke. The feathering paddle wheels are 22 feet outside diameter and 10 feet 3 in. face of bucket. The air and feed pumps are attached to and worked from main engine.

BOILERS.

Four in number, of the Return Tubular Type, 11 feet diameter and 11 feet 6 inches long over heads. Each boiler has two 41½ inch. outside diameter, Morison Suspension Furnaces. The boilers are fitted with the Howden Hot Draft and are designed for a working pressure of 175 lbs.

CABINS.

Spacious and elegant passenger accommodations are provided. One hundred and forty state rooms, including four parlor rooms, and large Pullman sleeping cabin, furnish sleeping

accommodation for 430 passengers.

The dining room placed on an upper deck has a seating capacity for over 100 persons.

The interior finish and decorations of the spacious halls and deck saloons are most elaborately executed, the main and gallery saloons being finished in Francis I. Renaissance, with the dining room in Louis XVI.

The entrance hall is decorated in Neo-Gree

with modern Renaissance details, with the smok-

ing room in Oriental treatment.

The refreshment and writing rooms will be in Elizabethian paneling of prima vera, natural

wood finish.

The main stair cases are in Honduras mahogany with wrought metal balustrades in hammered leaf work finished antique bronze, the main newels carrying bronze figures supporting electric torches.

MISCELLANEOUS.

A 700 light Electric Light Plant, with ornamental Electroliers in cabins, furnishes light throughout Steamer. All rooms and apartments particularly subjected to heat are provided with a system of artificial ventilation.